

APPROVED	O.G. FIG.	
BY	CLASS	SUBCLASS
DRAFTSMAN		

FIG. 1




FIG. 2





FIG. 3



APPROVED	O.G. FIG.	
BY	CLASS	SUBCLASS
DRAFTSMAN		

FIG. 4




FIG. 5





FIG. 6



APPROVED	O.G. FIG.	
BY	CLASS	SUBCLASS
DRAFTSMAN		





FIG. 8



# FIG. 9







FIG.10




ssi : section\_syntax\_indicator  
pi : private\_indicator  
rsvd : reserved  
psc : payload\_scramble\_indicator  
asc : address\_scramble\_indicator  
LSf : LLC\_SNAP\_flag  
cni : current\_next\_indicator

FIG.11

MAC ADDRESS	Ks_even	Ks_odd	Ks FLAG
08:00:46:01:07:24	0xC08F...25	0x90B3...AF	0
08:00:45:01:07:09	0x26D2...61	0xBA02...3C	1
01:00:5e:16:0:0	0x461E...67	0xDC1A...22	0

APPROVED	O.G. FIG.	
BY	CLASS	SUBCLASS
DRAFTSMAN		

# FIG. 12



APPROVED	O.G. FIG.	
BY	CLASS	SUBCLASS
DRAFTSMAN		

FIG.13

IP ADDRESS	bitmask	MAC address
133. 11. 9. 39	255. 255. 255. 225	08:00:46:01:07:24
133. 11. 20. 0	255. 255. 255. 0	08:00:46:01:07:09
226. 0. 0. 0	255. 255. 255. 224	01:00:5e:16:0:0

FIG.15

MAC ADDRESS	Ks_even	Ks_odd
08:00:46:01:07:24	0×C08F... 25	0×90B3... AF
01:00:5e:16:0:0	0×461E... 67	0×DC1A... 22

FIG.16

113

VERS	HLEN	SERVIE TYPE	TOTAL LENGTH	
IDENTIFICAION			FLAGS	FRAGMENT OFFSET
TIME TO LIVE		PROTOCOL	HEADER CHECKSUM	
SOURCE IP ADDRESS				
DESTINATION IP ADDRESS				
IP OPTIONS (IF ANY)				PADDING
DATA				
. . . . .				

# FIG. 14




FIG. 17




FIG. 18

